

SPECIFICATION OF PORTABLES

Project Description	
Supply of Portables	
	ZIPTECH

• Main Specifications :

Brand	ZIPTECH (Commercial)					
	Floor M.Beams	IPE120				
	Floor S.Beams	Tube 40×40 mm	c.c	35		
	Structure	Tube 40×40 mm		1		
E	Dry area	Plywood 18 mm				
Floor sub layer	wet area	Cementboard 18 mm				
Floor finish layer	Rooms	Vinyl Roll or Mocket abu okda				
	Toilets	pilets Vinyl Roll				
External Walls	White Pre-painted Corrugared sheets					
Internal Walls	Rooms	looms PVC cladding strips 25 cm wide				
	Toilets PVC cladding strips 25 cm wide					
Walls Insulation	FR Expanded polyeterene sheet 4cm					
Walls Thickness	60 mm (approximately)					
Roof	White Pre-painted Corrugared sheets					
Ceiling	Gypsum Tiles 60x60					
Roof Insulation	25 mm thk fiber glass with aluminum foil					
External Door	steel door laminated with steel sheets of both sides					
Internal Doors	Rooms MDF laminated with PVC					
	Toilets Single Aluminuim					
Doors Accessories	Complete set of fittings with U-Shape Steel Sheet Door Frame, Door Handle, Door Latch & Door Jamb, Keys, and Hinges					
Paint & Welding	All Steel welded according to structural welding practice and cleaned with primer					
Windows	Rooms	Aluminium sliding (Single glaze) (90×90)				
	Toilets					
Toilets	Ceramic European Toilet with Ceramic wash basin (pedestal type)					
Accessories	Faucet Mixer (hot & cold) and Mirror with Shelf					
Pantry / Kitchen	Single Stainless Steel Sink 50 ×100 cm with base PVC cabinet					
Main Panel Board	Design will be according to the building requirments					
Lighting Rooms Spot Light- LED Toilets Spot Light- LED		Spot Light- LED	Spot Light- LED			
		Spot Light- LED				
switches and sockets	"All Legrand Brand"or the same degree of quality					
	Stranded Wire Gauge no. 14/2.5mm -Lightning					
Wiring	Stranded Wire Gauge no. 12/4mm -Sockets					
vviinig	Stranded Wire Gauge no. 10/6mm -A/C					
	All wiring are protected and routed by Flexible plastic Conduit and embedded into the wall.(cable tray not included)					